



## level probe 76 AH

**Part no. 53214**

**level probe 76 AH for overfill prevention system (WHG)**

### benefits

- type approved in conjunction with the transducers UFS 01, NB 220 H and NB 220 QS as part of an overfill prevention system
- High-temperature version for operating temperature range up to 80 °C

### Application

Level probe for transducers as part of an overfill prevention system for stationary tanks and stationary-use tanks used to store water-polluting liquids with a flash point of > 55 °C (see product description UFS 01 for list of substances).

### Description

Approved as part of an overfill prevention system together with level transducers UFS 01 and NB 220 H. The level probe type 76 AH consists of a probe tube with a stainless steel-encapsulated PTC thermistor sensor at the lower end, a junction box and a screw fitting. Tube length 100 to 3,000 mm in increments of 100 mm. Standard lengths up to 500 mm. The overfill prevention system must be set up in such a way that a visual alarm and a sufficiently loud audible alarm are triggered when the maximum permissible level is reached.

### Technical Specifications

#### Material

junction box: Brass

Probe tube: stainless steel 304 or 316 Ti

Screw fitting: Brass

PTC thermistor: stainless steel-encapsulated

#### Process connection

Connection thread G $\frac{3}{4}$

#### Operating temperature range

Medium: -25/+80 °C

#### Degree of protection

IP 54 (EN 60529)

#### approval

DIBt: Z-65.11-185

## Versions

	Length	Length	Part no.
level probe 76 AH	500 mm		53214

-  in-stock items
-  Non-stock items