



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

**No: FIRE/3-CPR/ 2014**

Substrate: Mortar M1

Primer: No primer and Sikaflex Primer 3N

1. Identification Code	<b>Everbuild Firemate Intumescent Sealant</b> <b>Codes: FIRE/FIREMATEBN/FIREMATEGY</b>
2. Type, Batch and/or Serial Number	<b>- For batch number - see packaging</b>
3. Intended use	<b>Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements</b>
4. Manufacturer	<b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW</b>
5. Authorised Representative	<b>Not Applicable</b>
6. Assessment and Verification of Constancy of Performance	<b>System 3</b>
7. Notified Body and Tasks	<b>Ginger CEBTP Notified Body No. 00074</b>
8. European Technical Assessment	<b>Not Applicable</b>
9. Declared Performance	<b>TO EN15651-1 (2012)</b>
Type	<b>F INT-EXT</b>
Classification	<b>F7.5P</b>
Reaction to Fire	<b>Class E</b>

Loss of Volume ISO10563	<b>≤45%</b>
Resistance to flow ISO7390	<b>≤3 mm</b>
Adhesion/cohesion properties after water immersion (23°C) ISO 10591	<b>≥25%</b>
Adhesion / cohesion at constant temperature (ISO9046)	<b>NF</b>
Durability ISO 8339, ISO9046 and ISO 10591	<b>Pass</b>

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: P.R. Thomas – R&D Manager



Dated: Leeds, 7/10/15