

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1 Product identifier**

Trade name : Resiblock Original Natural

### **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Product use : Product is not intended for consumer use

### **1.3 Details of the supplier of the safety data sheet**

Company : Everbuild – A Sika Company  
Site 41  
Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds  
West Yorkshire LS9 0SW  
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

### **1.4 Emergency telephone number**

Emergency telephone number : 0044 113 240 3456 (office hours only)

---

## **SECTION 2: Hazards identification**

### **2.1 Classification of the substance or mixture**

Type of product : Mixture

#### **Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 3	H331: Toxic if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2, hearing organs	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

**2.2 Label elements**

**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal word : Danger

Hazard statements :

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.

Precautionary statements :

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
<b>Prevention:</b>	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P271	Use only outdoors or in a well-ventilated area.
<b>Response:</b>	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
<b>Storage:</b>	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
<b>Disposal:</b>	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

P501

Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

- 215-535-7 xylene
- 247-722-4 m-tolyldiene diisocyanate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
xylene 1330-20-7 215-535-7 01-2119488216-32-XXXX Contains: ethylbenzene <= 25 %	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 Asp. Tox.1; H304	>=80
2-(2-hydroxypropoxy)propanol 106-62-7 203-416-2	Skin Irrit.2; H315 Eye Irrit.2; H319	>= 10 - < 20
m-tolyldiene diisocyanate 26471-62-5 247-722-4 01-2119454791-34-XXXX	Carc.2; H351 Acute Tox.1; H330 Eye Irrit.2; H319 STOT SE3; H335 Skin Irrit.2; H315 Resp. Sens.1; H334 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 0,25 - < 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.

- If inhaled : Call a physician or poison control centre immediately.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.  
Asthmatic appearance  
Cough  
Respiratory disorder  
Allergic reactions  
Excessive lachrymation  
Erythema  
Headache  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Risk of serious damage to the lungs (by aspiration).  
irritant effects  
sensitising effects
- May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
Toxic if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure if inhaled.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Country GB 000000602482

4 / 14

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical

Unsuitable extinguishing media : Water, High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

- Advice on safe handling : Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Prevent unauthorized access. Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.
- Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
xylene	1330-20-7	STEL	100 ppm 441 mg/m3	GB EH40
		TWA	50 ppm 220 mg/m3	GB EH40
		TWA	50 ppm 221 mg/m3	2000/39/EC
		STEL	100 ppm	2000/39/EC

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

m-tolylidene diisocyanate	26471-62-5	TWA	442 mg/m <sup>3</sup>	GB EH40
		STEL	0,02 mg/m <sup>3</sup>	GB EH40
			0,07 mg/m <sup>3</sup>	GB EH40

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT
m-tolylidene diisocyanate	26471-62-5	urinary diamine: 1 µmol/mol creatinine (Urine)	Post task	GB EH40 BAT

## 8.2 Exposure controls

### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm),  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Use respiratory protection when vapours/aerosols are released. Suitable respiratory protection at high concentrations or longer exposure: self-contained breathing apparatus. Suitable respiratory protection for low concentrations: ABEK-filter.

### Environmental exposure controls

General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: clear
Odour	: No data available
Odour Threshold	: No data available
Flash point	: 40 °C
Autoignition temperature	: 465 °C
Decomposition temperature	: No data available
Lower explosion limit (Vol-%)	: 1 %(V)
Upper explosion limit (Vol-%)	: 7 %(V)
Flammability	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: 7,9993 hPa

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017

Version 0.0

Print Date 20.10.2017



BUILDING TRUST



Density	:	0,93 g/cm <sup>3</sup> at 20 °C
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Viscosity, dynamic	:	30 mPa.s
Viscosity, kinematic	:	> 7 mm <sup>2</sup> /s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Toxic if inhaled.

#### Components:

#### xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.700 mg/kg

### m-tolylidene diisocyanate:

Acute inhalation toxicity : LC50 (Rat): 0,107 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.

### Aspiration toxicity

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### xylene :

Toxicity to fish : 3,3 mg/l, 96 h, *Oncorhynchus mykiss* (rainbow trout)

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

**ADR**

14.1 UN number : 1866  
14.2 UN proper shipping name : RESIN SOLUTION  
14.3 Transport hazard class(es) : 3  
14.4 Packing group : III  
Classification Code : F1  
Labels : 3  
Tunnel restriction code : (D/E)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017



BUILDING TRUST



Version 0.0

Print Date 20.10.2017

**14.5 Environmental hazards** : no

### IATA

**14.1 UN number** : 1866  
**14.2 UN proper shipping name** : Resin solution  
**14.3 Transport hazard class(es)** : 3  
**14.4 Packing group** : III  
Labels : 3  
**14.5 Environmental hazards** : no

### IMDG

**14.1 UN number** : 1866  
**14.2 UN proper shipping name** : RESIN SOLUTION  
**14.3 Class** : 3  
**14.4 Packing group** : III  
Labels : 3  
EmS Number 1 : F-E  
EmS Number 2 : S-E  
**14.5 Marine pollutant** : no

### 14.6 Special precautions for user

No data available

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information: All substances contained in our Products are  
- preregistered or registered by our upstream suppliers, and/or  
- preregistered or registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
H2	ACUTE TOXIC	50 t	200 t

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017

Version 0.0

Print Date 20.10.2017



BUILDING TRUST



P5c	FLAMMABLE LIQUIDS	5.000 t	50.000 t
VOC-CH (VOCV)	: 80,01 %		
VOC-EU (solvent)	: 80,01 %		

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations : Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

### Full text of H-Statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H412	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Resiblock Original Natural

Revision Date 20.10.2017

Version 0.0

Print Date 20.10.2017



BUILDING TRUST



Resp. Sens.	Respiratory sensitisation
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

### Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 3	H331
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Resp. Sens. 1	H334
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304

### Classification procedure:

Based on product data or assessment
Calculation method
Based on product data or assessment

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !